



- 6000 watts continuous power
- 12000 watts peak power
- Provides 50 Amps
- Anodized aluminum case provides durability
- Built-in Cooling Fan
- Internal, Replaceable 30 Amp spade-type Fuses
- FOUR - 3 Prong 120 volt AC outlet
- Overload Indicator
- Power ON/OFF Switch
- Optional Remote Switch

Specifications	12 Volt	24 Volt
Continued Power	6000W	6000W
Peak Load Power Rate	< 12000W	< 12000W
No Load Current Draw	< 2.0A	< 2.0A
Input DC Voltage Range	11-15V	22-30V
Output Voltage Range	117 +/- 10%	117 +/- 10%
Output Frequency Range	60 +/- 3Hz	60 +/- 3Hz
Max Outer Temperature	< 65 C	< 65 C
Max Power Efficiency	> 90%	> 90%
High Voltage Cut Off Level	15.5 +/- 1V	30.5 +/- 1V
Low Voltage Alarm Level	10.5 +/- 0.5V	21 +/- 0.5V
Low Voltage Cut Off Level	10 +/- 0.5V	20.5 +/- 0.5V
Short Protect	Yes	Yes
Overload Protect	Yes	Yes
Dimension (LxWxH) in	27.5 x 6.5 x 9.1 in.	27.5 x 6.5 x 9.1 in.
Weight	28.00 lbs	28.00 lbs
Input Voltage	DC 12V	DC 24V